

American River Flood Control District

Purchase of International Dump Truck from Sourcewell Cooperative Purchasing

Staff Report

Discussion:

The District needs to acquire a new dump truck for general use and to replace a 2010 International dump truck currently in use. The 2010 International no longer meets California air quality standards and will not be able to be registered in 2023. Staff has identified the most optimal vehicle to serve in this role as a new 2024 International dump truck. This truck will be used for material hauling and heavy towing.

State law requires that purchases over \$25,000 must be made through a public bidding process. This ensures that public funds are spent on items at the best available price. In the past, the District has acquired large equipment through solicitation of public bids or through cooperative purchasing programs such as the CA Multiple Award Schedule or Sourcewell. Cooperative purchasing programs have already bid the items for sale publicly and include discounted rates based on collective bidding.

District staff recently obtained a cost quote for acquisition of this piece of equipment through Sourcewell. The following cost quote is the best available price for this equipment:

1. New 2024 International Dumptruck with Enoven dump body
Complete with tax and fees = **\$212,803.19**

Due to current backlog on vehicle production, this order may take 10-12 months to be filled.

Recommendation:

The General Manager recommends that the Board of Trustees approve the purchase of the specified equipment from Sourcewell.

Riverview International Trucks, LLC
2445 Evergreen Ave.
West Sacramento
California 95691
916-371-3110



Date	08/05/22		SS# / TIN
Buyer	American River Flood Control District		
Address	185 Commerce Circle		
City, State	Zip	County	Tax Rate
Sacramento, CA	95815	Sacramento	8.750%
ATTN:			
Ship To Address	same		

Stock Number	Mileage
Driver's License Number	State
License Plate Number	

Year	New/Used	Make	Model	Serial #/Description	Axles	Stock Number	Sales Price
2024	New	Intl	HX	TBD - New Build - chassis specs attached	3	TBD	\$195,585.00
				* Includes Enoven installed 15' dump and all related components listed in specs attached			

Registration				Purchase	
Registered Owner			Sales Price	1	\$195,585.00
Address			Doc Fee	2	\$80.00
Legal Owner			Sales Tax	3	\$17,120.69
Address			Excise Tax	4	\$0.00
Trades #1 #2			CA Tire Fee \$1.75/TIRE	5	\$17.50
Make			Sale Price Including Taxes	6	\$212,803.19
Yr./Mdl			Down Payment Cash	7a	\$0.00
Chassis#			Trade In Net allowance	7b	\$0.00
Body Typ			Total Down Payment	8	\$0.00
Allowance	Amounts \$0.00	Amounts \$0.00	Forward Balance	9	\$212,803.19
Amt.Owed	\$0.00	\$0.00	Optional Service Contract	10	\$0.00
Lien Holder Information			Vin Verification Fee		\$0.00
Net Trade Allowance	\$0.00	\$0.00	License Fees	11	\$0.00
			Balance Due		\$212,803.19

Source of Payment:	Out of State Delivery Required? No	If yes, City and State of delivery:
Optional Service Contract info - Form/Contract# Month/miles/hours?	Mileage at delivery: Unladen weight:	Body type: DUMP GCVW/GVWR: 54,600 GVWR
Accepted By:(Management)	**Pricing is subject to future surcharges and/or increases due to government regulations or as market conditions change.**	
Order Taken By:	Purchaser Signature:	Date:

Note: This order is subject to the acceptance of the dealer to which it is addressed, and is subject to Written acceptance by its Sales Manager. Purchaser's deposit will be returned if not accepted. If Vehicle(s) is used the vehicle(s) is sold "as is" with no warranty. Purchaser acknowledges receipt of exact copy of this order.

INTERNATIONAL®**August 05, 2022****Prepared For:**

American River Flood Control
 Richard Marck
 165 Commerce Cir.
 Sacramento, CA 95815-4226
 (916)929 - 4006
 Reference ID: N/A

Presented By:

RIVERVIEW INTL TRKS, LLC
 Jason Farrell
 2445 EVERGREEN AVENUE
 WEST SACRAMENTO CA 95691 -
 (916)371-3110

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2023 HX620 SBA (HX620)

AXLE CONFIG: 6X4
APPLICATION: Construction Dump
MISSION: Requested GVWR: 54000. Calc. GVWR: 54600. Calc. GCWR: 125000
DIMENSION: Wheelbase: 205.00, CA: 136.00, Axle to Frame: 55.00
ENGINE, DIESEL: {Cummins X15 430 V} Productivity Series, EPA 2021, 430HP @ 1900 RPM, 1650 lb-ft Torque @ 950 RPM, 2000 RPM Governed Speed, 441 Peak HP (Max)
TRANSMISSION, AUTOMATIC: {Allison 4000 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway
CLUTCH: Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING: {Meritor MFS-14-143A} Wide Track, I-Beam Type, 14,600-lb Capacity
AXLE, REAR, TANDEM: {Meritor MT-40-14X-4DFR} Single Reduction, 40,000-lb Capacity, .433"(11mm) Wall Housing Thickness, R Wheel Ends Gear Ratio: 5.29
CAB: Conventional, Day Cab
TIRE, FRONT: (2) 315/80R22.5 Load Range L HAU 3 WT (CONTINENTAL), 480 rev/mile, 68 MPH, All-Position
TIRE, REAR: (8) 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, TANDEM: {Hendrickson HMX EX 400} Walking Beam, 40,000-lb Capacity, 54" Axle Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings
PAINT: Cab schematic 100LZ
 Location 1: 9219, Winter White (Std)
 Chassis schematic N/A

INTERNATIONAL®**Vehicle Specifications**
2023 HX620 SBA (HX620)**August 05, 2022****Description**

Base Chassis, Model HX620 SBA with 205.00 Wheelbase, 136.00 CA, and 55.00 Axle to Frame.

AXLE CONFIGURATION

AXLE CONFIGURATION {Navistar} 6x4

Notes

: Pricing may change if axle configuration is changed.

ENGINE

ENGINE, DIESEL {Cummins X15 430 V} Productivity Series, EPA 2021, 430HP @ 1900 RPM, 1650 lb-ft Torque @ 950 RPM, 2000 RPM Governed Speed, 441 Peak HP (Max)

CARB EMISSION WARR COMPLIANCE for Cummins X15 Engines Less than or Equal to 500 HP

CARB IDLE COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood

EMISSION, CALENDAR YEAR {Cummins X15} EPA, OBD and GHG Certified for Calendar Year 2022

RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler

Includes

: RADIATOR HOSES Premium, Rubber

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

Includes

: FAN Nylon

AIR CLEANER Dual Element, with Integral Pre-Cleaner, Engine Mounted

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

ENGINE CONTROL, REMOTE MOUNTED for X15 Engines

FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted

HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type

RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System

TRANSMISSION

TRANSMISSION, AUTOMATIC {Allison 4000 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223

NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released

OIL COOLER, AUTO TRANSMISSION {Modine} Remote Mounted; Not for use with Retarder

SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming

TRANSMISSION OIL Synthetic; 63 thru 76 Pints

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission

CLUTCH

INTERNATIONAL®**Vehicle Specifications**
2023 HX620 SBA (HX620)**August 05, 2022****Description**

CLUTCH Omit Item (Clutch & Control)

REAR AXLES, SUSPENSIONS

AXLE, REAR, TANDEM (Meritor MT-40-14X-4DFR) Single Reduction, 40,000-lb Capacity, .433"(11mm) Wall Housing Thickness, R Wheel Ends . Gear Ratio: 5.29

SUSPENSION, REAR, TANDEM (Hendrickson HMX EX 400) Walking Beam, 40,000-lb Capacity, 54" Axle Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings

TRANSVERSE TORQUE RODS (Hendrickson) TRAAX Rod, Transverse Only

FRONT AXLES

AXLE, FRONT NON-DRIVING (Meritor MFS-14-143A) Wide Track, I-Beam Type, 14,600-lb Capacity

FRONT SUSPENSIONS

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 16,000-lb Capacity, with Shock Absorbers

CABS, COWLS, BODIES

CAB Conventional, Day Cab

Includes

- : CAB REAR SUSPENSION Air
- : CLEARANCE/MARKER LIGHTS (5) LED Roof Mounted
- : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window
- : CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area
- : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger
- : COURTESY LIGHT (2) Driver and Passenger Door Mounted
- : DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console
- : FLOOR COVERING Rubber, Black
- : GLASS, ALL WINDOWS Tinted
- : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side
- : GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side
- : READING LIGHT, CAB Located in Overhead Console
- : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door

ACCESS, CAB Aluminum, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab or Sleeper Cab

AIR CONDITIONER with Integral Heater and Defroster

Includes

- : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps

CAB INTERIOR TRIM Diamond, for Day Cab

FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

GAUGE CLUSTER Premium Level; English with English Electronic Speedometer

Includes

- : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for
- : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure
- : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)

INTERNATIONAL®**Vehicle Specifications**
2023 HX620 SBA (HX620)**August 05, 2022****Description**

GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel, Mounted in Instrument Panel

GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

GAUGE, OIL TEMP, ENGINE

GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left and Right Side at B-Pillar

INSTRUMENT PANEL Wing Panel

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

MIRROR, CONVEX, LOOK DOWN Right Side, Black, 6" x 10.5"

MIRRORS (2) C-Loop, Heated, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width

Notes

: Mirror Dimensions are Rounded to the Nearest 0.5"

MIRROR, CONVEX, HOOD MOUNTED (2) Right and Left Sides, Black, 7.5" x 7"

MODESTY PANEL Painted

SEAT, DRIVER {ISRI} Series 300, Air Suspension, High Back, Vinyl, Single Chamber Lumbar, Inboard Armrest, Suspension Cover, Fore/Aft Isolator, Cushion Extension, Seat Tilt

SEAT, TWO-MAN PASSENGER {National} Mid Back, Fixed Back, Vinyl, with Under Seat Storage

WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature

FRAMES

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL

BUMPER, FRONT Contoured, Steel, Painted, Heavy Duty, for HX

CROSSMEMBER, REAR Relocated to End of Frame

TOW HOOK, FRONT (2) Frame Mounted; 80,000-lb. Total Capacity

WHEELBASE RANGE 191" (485cm) Through and Including 236" (600cm)

BRAKES

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon

: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel

: PARKING BRAKE VALVE For Truck

: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4

: SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6

BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake

AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System

BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity

BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn

SLACK ADJUSTERS, FRONT {Gunite} Automatic

INTERNATIONAL®Vehicle Specifications
2023 HX620 SBA (HX620)**August 05, 2022**Description

DUST SHIELDS, FRONT BRAKE for Air Cam Brakes

BRAKES, REAR {Meritor 16.5X8.625 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 8.625", 23,000-lb Capacity per Axle

BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Sqn Spring Brake

SLACK ADJUSTERS, REAR {Gunitite} Automatic

PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type

DUST SHIELDS, REAR BRAKE for Air Cam Brakes

AIR COMPRESSOR {Cummins} 18.7 CFM

AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration

AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab

AIR TANK LOCATION (2) : One Mounted Under Each Rail, Front of Rear Suspension, Parallel to Rail

DRAIN VALVE (2) {Berg} with Pull Chains, for Air Tanks

TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck

STEERING

STEERING GEAR (2) {Sheppard M100/M80} Dual Power

STEERING COLUMN Tilting and Telescoping

STEERING WHEEL 4-Spoke; 18" Dia., Black

DRIVELINES

DRIVELINE SYSTEM {Dana Spicer} SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4

EXHAUST SYSTEMS

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Cab Mounted Right Side

AFTERTREATMENT COVER Aluminum

ENGINE COMPRESSION BRAKE {Cummins} Interbrake For Cummins Signature/ISX/X15 Engines; Furnished with Engine

EXHAUST HEIGHT 11' 6"

MUFFLER/TAIL PIPE GUARD (1) Aluminum

TAIL PIPE (1) Turnback Type

ELECTRICAL SYSTEMS

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

INTERNATIONAL®**Vehicle Specifications
2023 HX620 SBA (HX620)****August 05, 2022****Description**

: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted

ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount

ANTENNA for Increased Roof Clearance Applications

BATTERY BOX Aluminum, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Right Side Back of Cab

BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

CB RADIO Omit Power Feeds, Power Source and Wiring

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket

HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

HEADLIGHTS Halogen

HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on

HORN, AIR Single, Located Under Cab

HORN, ELECTRIC Disc Style

POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) with USB Port, Located in the Instrument Panel

RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input

SPEAKERS (2) 6.5" Dual Cone Mounted in Doors

STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start

STOP, TURN, TAIL & B/U LIGHTS {Weldon} Multi-Function LED Lamp, Mounted Outside Rails, Includes LED License Plate Light

TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights

TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch

TURN SIGNAL SWITCH Self-Canceling

WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time

FRONT END

FRONT END Tilting, Composite

FENDER EXTENSIONS Rubber

GRILLE Black Vertical Accent Bars, with Black Mesh

LOGOS EXTERIOR Model Badges

LOGOS EXTERIOR, ENGINE Badges

SPEEDOMETER, TOOLS, MISC

COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360

INTERNATIONAL®**Vehicle Specifications**
2023 HX620 SBA (HX620)**August 05, 2022****Description**

PAINT SCHEMATIC, PT-1 Single Color, Design 100

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

FUEL TANKS

FUEL TANK Non-Polished Aluminum, 24" Dia, 60 US Gal (227L), Mounted Left Side, Under Cab

DEF TANK 10.6 US Gal (40L) Capacity, Frame Mounted Outside Left Rail, Under Cab

FUEL HEATER (Cummins) Omit Plumbing for TRV on Cummins Engines

FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor

WHEELS, TIRES - FRONT

WHEELS, FRONT {Accuride 29039} DISC; 22.5x9.00 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs, Non-Standard Offset, with .5" Thick Disc

(2) TIRE, FRONT 315/80R22.5 Load Range L HAU 3 WT (CONTINENTAL), 480 rev/mile, 68 MPH, All-Position

WHEELS, TIRES - REAR

WHEELS, REAR {Accuride 29169} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with .472" Thick Increased Capacity Disc and Steel Hubs

(8) TIRE, REAR 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive

BODY INTEGRATION

BDY INTG, REMOTE POWER MODULE Mounted Inside Cab Behind Driver Seat, Up to 6 Outputs & 6 Inputs, Max 20 amp per Channel, Max 80 amp Total; Includes 1 Switch Pack with Latched Switches

BDY INTG, INDICATOR LIGHTS (2) 1 for Body Up, 1 for Gate Open, Includes Audible Alarm, Programmable Mode for Various Switch Actions. (Requires 2 Remote Power Module Inputs)

Services Section:**WARRANTY**

WARRANTY Standard for HX520, HX620, Effective with Vehicles Built January 1, 2021 or Later, CTS-2015B

Body/Allied Equipment**Description**

Enoven installed dump body

Goods Purchased**Description**



Enoven Truck Body + Equipment

Quote #: 81223 ^{Item 6}

2904 Duluth St
West Sacramento, CA 95691
916-372-9692

Date: 8/5/2022
CustID: 31637

Thank you for the opportunity to quote your business, please call if you have any questions.

American River FCD
185 Commerce Circle
Suite D
Sacramento, CA 95815

American River FCD
185 Commerce Circle
Suite D
Sacramento, CA 95815

Attn: Ross Kawamura
916-708-7017
ross@arfed.org

Qty>=	Description	Unit Price	Ext Price
1	<p>Dump Body: 15', BeauRoc DH, 15-3642-HL</p> <p>(REQUIRES 132" C/T)</p> <ul style="list-style-type: none"> - 11 to 13 cu.yd. - Floor: 1/4" HARDOX 450 with 8" X 3/16" formed trapezoidal long sills, NO CROSSMEMBERS - Sides: 36" tall, 3/16" HARDOX 450 with 3" X 4" X 1/4" tubing top rail, pressed horizontal brace, and full length fender <ul style="list-style-type: none"> - 2" X 6" wood cheater boards installed - Fold down ladder at front corner, driver side, and at rear corner, passenger side - (12) tarp hooks mounted under mid rail, (6) per side - Headsheet: 68" tall, 3/16" HARDOX 450 with 24" X 3/16" cab shield <ul style="list-style-type: none"> - Tool holders mounted to front of headboard, one per side - ECCO 5585A 15" Amber LED Mini-Lightbar mounted to riser bracket on cab shield with 1" X 1" tubing guard wired to OEM "BEACON LAMP" dash switch - Tailgate: 42" tall, 1/4" HARDOX 450 with pressed horizontal brace, Air Release and Internal Air Highlift wired to switches in console with RED safety covers <ul style="list-style-type: none"> - 8" bolt on spreader apron with spreader chains - 2.5" Red LED Clearance lamps at top of rear posts <ul style="list-style-type: none"> - (2) ECCO 3965A Amber LED Strobe lamps at top of rear posts wired to OEM "STROBE LAMP" dash switch - 6" LED S/T/T and B/U lamps in rear posts - 2.5" Red LED Marker lamps in sides of rear posts - OEM S/T/T/BU lamps at end of frame - Red LED ID Lamp Bar mounted to top of hitch plate <ul style="list-style-type: none"> - LED License Plate lamp mounted to hitch plate - Front trunnion mounted, base lift Mailhot G3 135-5.7-3 telescopic cylinder giving 45 tons lifting capacity at 50 degree dump angle with 12" overhang <ul style="list-style-type: none"> - Hotshift PTO wired to OEM dash switch with direct mount dump pump - Cable dump controls mounted between seats in cab - 25gal steel hydraulic reservoir with internal 	\$42,937.00	\$42,937.00

Qty>=	Description	Unit Price	Ext Price
	<ul style="list-style-type: none"> return line filter mounted to frame rail, driver side - Body up lamp in dash - Body prop - Back up alarm - "ENOVEN" mud flaps aft of tires with front plastic splash guards - (2) ECCO 3706A Amber LED Strobe lamps mounted in front grill wired to OEM "STROBE LAMP" dash switch - Painted Black - Installed, Weighed, and Certified 		
1	Accessories: 5/8" Buck Plate with Hitch <ul style="list-style-type: none"> - 45ton Air Pintle Hitch (Customer to Specify Height) - (2) 1" D-Rings - 7-Way ABS Round Pin Trailer Socket mounted to top left of plate - 7-way Flat Pin Trailer Socket mounted to top passenger side of plate wired to Tekonsha Prodigy electric brake controller mounted in cab - Glad Hands split mounted to top of plate, Red on left and Blue on right - Red LED ID Lamp Bar mounted to top center of plate - LED License Plate lamp mounted to top of plate - Integrated underride protection, as needed - Painted Black 	\$2,739.00	\$2,739.00
1	Accessories: Pull Tarps Electric Tarping System <ul style="list-style-type: none"> - SuperShield enclosure mounted to top of headboard - HD Mesh Tarp with grommets - Steel arms attached to sides of body - Second arm kit - Switch in cab 	\$4,140.00	\$4,140.00
1	Accessories: Toolbox, 36" <ul style="list-style-type: none"> - 36" X 18" X 18" steel toolbox mounted to frame rail, passenger side - Powdercoated Black - SSTL spring toolholder mounted to top of toolbox 	\$979.00	\$979.00
1	Accessories: Cone Holder <ul style="list-style-type: none"> - Post style coneholder mounted to frame rail, driver side aft of hydraulic tank - Painted Black 	\$490.00	\$490.00

Qty>= Description

Unit Price

Item #
Ext Price

TOTAL

\$51,285.00

This Quote is good for 30 days. Acceptance of this Quote is confirmed and accepted by issuance of a Purchase Order, signing and returning this Quote, and/or delivery of a truck chassis to Enoven. This quotation was made expressly upon your request and is confidential and non transferable. If provided, estimated delivery dates are estimates only; actual delivery dates depend on a variety of factors that may/may not be within the direct control of Enoven. FUEL SERVICE CHARGE - IF A TRUCK IS DELIVERED WITH LESS THAN 1/4 TANK OF DIESEL/GASOLINE OR LESS THAN 1,500PSI CNG, A \$100.00 FUEL SERVICE CHARGE WILL BE ADDED TO THE FINAL INVOICE. For complete Terms and Conditions please go to www.enoven.com.

Terms of Sale:

Net10

Enoven Truck Body + Equipment

Authorized by: senochian

Date: 8/5/2022

Printed: 8/5/2022 12:49:55 PM